

## SPECIFICATION SHEET



### 1. Product Identification

Field	Details
Product Name	<b>Titan AV 6002A Waterproof Hard Case</b>
SKU	<b>FXC-6002A</b>
GTIN	9359899004257
Warranty	2 Years
Country of Origin	Manufactured in China, QC tested in Australia

### 2. Dimensions & Weight

Specification	Measurement
External Dimensions (L x W x H)	550 x 420 x 205 mm
Internal Dimensions (L x W x H)	490 x 360 x 200 mm
Lid / Base Depth	50 mm / 150 mm

Internal Volume	35.3 L
Weight (Empty)	3 kg
Padlock Hole Diameter	7 mm

### 3. Construction & Materials

Component	Specification
Shell Material	High-impact Polypropylene (FX-2PP)
Foam Insert	1 × 90 mm pick-n-pluck + 1 × 40 mm pick-n-pluck + 1 × 10 mm solid base
Seal	EPDM O-ring watertight closure
Latches	Dual TUFF compression latches
Pressure Valve	Automatic pressure equalisation valve
Handle	Rubberised ergonomic carry handle
Hinges	Heavy-duty pinned hinges
Stackable	Yes

### 4. Environmental Performance

Parameter	Details
Ingress Protection	IP67 – dust-tight and waterproof up to 1 m for 30 min
Temperature Range	–30 °C to +80 °C
Vibration Resistance	Meets MIL-STD-810H Method 514.8
Drop Resistance	Meets MIL-STD-810H Method 516.8
Chemical Resistance	Resistant to oils, solvents, and mild acids (typical of polypropylene materials)

## 5. Functional Features

- Waterproof, dustproof & impact-resistant
- Auto pressure relief valve for air travel
- Lockable with 7 mm padlocks
- Customisable pick-n-pluck foam interior
- Stackable interlocking design
- Ideal for AV gear, tools, comms equipment and drones

## 6. Compliance & Labelling

Category	Statement
IP Rating	Certified to IEC 60529 (IP67) standard – verified by independent testing
MIL-STD Testing	Tested to MIL-STD-810H (Methods 503.7, 514.8, 516.8)
Australian Quality Assurance	Each batch QC tested and inspected in Titan AV's Brisbane facility
Environmental Responsibility	Manufactured using materials consistent with international environmental standards – supplier declarations held on file where available

*Version 1.0, Dated: 13/10/2025*